

Fike Corporation

MATERIAL SAFETY DATA SHEET



Product: IG-55

Version: 1.0

Date: April 1, 2003

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name	IG-55
Chemical Formula	N ₂ / Ar
Company Identification	Local filling station
Emergency Phone Numbers	Local filling station

COMPOSITION / INFORMATION ON INGREDIENTS

Substance / Preparation	Preparation
Components / Impurities	Contains no components or impurities which will influence the classification of the product
CAS No.	N/A
EEC No.	N/A
Specifications	
IG-55	Mixture of 50% - 52% N₂ and 48% - 50% Ar. H₂O ≤ 10ppm O₂ ≤ 10ppm in base components.

HAZARDS IDENTIFICATION

Hazards Identification	In high concentrations may cause asphyxiation. Compressed gas.
------------------------	---

FIRST AID MEASURES

Inhalation	In high concentrations may cause asphyxiation at high concentrations. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Remove victim to an uncontaminated area, wearing self-contained breathing apparatus. Keep victim warm and at rest. Seek medical assistance. Apply artificial respiration if breathing has stopped.
Skin / eye contact	Compressed gas directed at the skin can enter the body through small wounds or can even penetrate the skin, causing serious or fatal injuries. Seek medical advice immediately.
Ingestion	Ingestion is not considered a potential route of exposure.

Fike Corporation

MATERIAL SAFETY DATA SHEET



FIRE FIGHTING MEASURES

Specific Hazards	Exposure to fire may cause containers to rupture / explode. Call the Fire Department Non flammable.
Hazardous combustion products	None.
Suitable extinguishing media	All known extinguishants can be used.
Specific methods	If possible, stop flow of product. Move container away or cool with water from a protected position.
Special protective equipment For fire fighters	In confined spaces use self-contained breathing apparatus.

ACCIDENTAL RELEASE MEASURES

Personal precautions	Evacuate area. Use self-contained breathing apparatus when entering area unless atmosphere is proved safe. Ensure adequate air ventilation.
Environmental precautions	Provided it is safe to do so, try to stop release. Prevent from entering sewers, basements, and workpits or any place where accumulation can be dangerous.
Clean up methods	Ventilate area.

HANDLING AND STORAGE

Handling and Storage	Backflow of any contaminating substance into container must be prevented. Use only equipment specified as suitable for this product, its supply pressure and temperature. Contact your supplier if in doubt. Compressed gas cylinders are heavy and contain considerable stored energy. Use suitable equipment and handle with appropriate caution. Refer to suppliers. Keep containers below 50°C in a well-ventilated place.
----------------------	---

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limit Value – ELV	No ELV specified, but atmosphere must have a minimum 18% free oxygen
Personal Protection	Ensure adequate air ventilation.

Fike Corporation

MATERIAL SAFETY DATA SHEET



PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight	33.95
Melting point	-199.7°C
Boiling point	-190.1°C
Critical temperature	-134.7°C
Relative density gas	Heavier than air
Relative density liquid	N/A
Vapour pressure 20°C	N/A
Solubility in water	Negligible
Appearance / colour	Colourless gas
Odour	No odour warning properties
Auto ignition temperature	Not applicable
Flammability range	Non flammable
Other data	Vapour is heavier than air. May accumulate in confined spaces, particularly at or below ground level.

STABILITY AND REACTIVITY

Stability and Reactivity Stable under normal conditions.

TOXICOLOGICAL INFORMATION

General No toxicological effects from this product.
LC50/ ih (ppm) No acute toxicity

ECOLOGICAL INFORMATION

General No ecological damage is caused by this product.
Nitrogen and Argon are natural components of air. Nitrogen constituting approximately 78% and Argon approximately 0.9% of the earth's atmosphere.

DISPOSAL CONSIDERATIONS

General To atmosphere in well ventilated area. Consider noise and pressure hazards. Do not discharge into any place where its accumulation could be dangerous.
Contact your Fike Corporation supplier if guidance is required.

Fike Corporation

MATERIAL SAFETY DATA SHEET



TRANSPORT INFORMATION

UN No.	1981
Class / Div.	2.2
Emergency Action Code	None specified
ADR / RID ITEM No. 1	2.1a
IMDG page	2141
IMO	EMS 2 - 04
ADR / RID Hazard No.	Not specified
Labelling ADR	Non flammable non-toxic gas.
Other transport information	Avoid transport on vehicles where the loads space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do at an emergency.

Before transporting product containers ensure:

- cylinder valve is closed and not leaking
- valve outlet cap or plug (where provided) is correctly fitted
- adequate ventilation
- compliance with applicable regulations.

REGULATORY INFORMATION

Number in annex 1 of Dir. 67/548	Not included in Annex 1.
EC Classification	Not classified as a dangerous substance.
EC Labelling (Symbols, R & S phrases)	
- Symbols	Compressed gas.
Risk Phrases	Asphyxiate in high concentrations.
Safety Phrases	Do not breathe the gas. Keep containers in a well-ventilated place.

OTHER INFORMATION

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details in this document are believed to be correct at present. While great care has been taken in the preparation of this information, no liability for injury, damage or non-compliance with any legislation or directive arising from its use can be accepted.

This sheet does not constitute or substitute for the user's own assessment of workplace risk as required by other health and safety legislation.