

PXW Two Way In Wall Chemical Gas Extract Unit



The PXW Two Way In Wall Chemical Gas Extract range is designed to provide combined pressure relief and gas extraction for chemical gasses. These easy to install units offer a cost effective solution for post discharge gas extraction.

Each unit includes a 4 hour fire rated AFP DUX Two Way pressure relief damper as standard. The additional free vent area of the pressure relief damper can be factored into the enclosures overall requirement.

The unit is supplied in kit form for fitting at low or high level within the risk.

Additional standard DUX or SHX pressure vents can be supplied for fresh air makeup.

PRODUCT SPECIFICATION

Product Specification		
Product Code	PXW300 Two Way	PXW500 Two Way
Free Vent Area	Neg. 0.077m ² Pos 0.047m ²	Neg. 0.216m ² Pos 0.128m ²
Extraction Per Hour	2200m ³	4300m ³
Overall WxHxD	550x550x380mm	660x660x380mm
Hole Cut Out WxH	360x350mm	560x550mm
Weight	29.5kg	54kg

PRODUCT INFORMATION

- Steel powder coated construction RAL 9003 signal white
- Manufactured to ISO9001
- The products carry a 5 year guarantee.
- The PXW comes with wall liner, wall liner extension, Helios SPW fan, KAC call point key switch and external louvre.