

# VLF-500



# VESDA®

## PRODUCT OVERVIEW

VESDA VLF-500 detector is a very early warning smoke detector designed to protect small, business-critical environments of less than 500 m<sup>2</sup> (5000 sq. ft.)

The detector works by continually drawing air into sampling holes in a pipe network. The air is filtered and passed into a detection chamber where light scattering technology detects the presence of very small amounts of smoke. Detector status information is communicated on the detector display and via relays or optional interface cards.

## OUT-OF-THE-BOX OPERATION

The VLF can be installed and commissioned out-of-the-box without the need for a special interface or software programming tools.

In operation, the unique Smoke Dial display provides the user with an instant understanding of a smoke event, even from a distance. Should a fault occur, the user simply opens the field service door and activates the Instant Fault Finder feature to determine the specific fault condition. This information can then be passed onto their fire service company, ensuring that service technicians arrive onsite fully prepared.

## ULTRASONIC FLOW SENSING

The patent-pending Ultrasonic Flow Sensing used in the VLF provides a direct reading of the sampling pipe flow rate. The system is immune to air temperature and pressure changes and is unaffected by contamination. The VLF is the first air sampling smoke detector to use ultrasonic flow sensing.

## FEATURES

- Out-of-the-Box Installation and Commissioning
- Ultrasonic Airflow Sensing
- Laser-Based Absolute Smoke Detection
- Pre-engineered pipe network designs
- Programmable Alarm Thresholds
- Clean air barrier optics protection
- Instant Recognition Display
- Instant Fault Finder™
- AutoLearn™ Smoke
- AutoLearn™ Flow
- Field Service Access Door
- Multiple Event Logging in separate logs
- Event log – up to 18000 events
- Offline/online configuration capability
- Up to 500 m<sup>2</sup> (5000 sq. ft.) coverage\*

## LISTINGS/APPROVALS

- UL
- ULC
- FM
- CFE
- LPCB
- VdS
- VNIPO
- AFNOR
- ActivFire
- CE - EMC and CPD
- EN 54-20
- Class A (30 holes / 0.05% obs/m)
- Class B (30 holes / 0.15% obs/m)
- Class C (30 holes / 0.32% obs/m)
- Classification of any configuration is determined using ASPIRE2.

# SPECIFICATIONS

## Input Power

Voltage:	24V DC Nominal (18-30 V DC)
Current @ 24 VDC:	410 mA nominal, 490 mA in alarm
<b>Dimensions</b> (W x H x D)	255 mm x 185 mm x 90 mm (97/8 in x 71/8 in x 31/2 in)
Weight	Approx. 2 kg (4.4 lbs)
IP Rating	IP30
Mounting	Upright, inverted or horizontal
<b>Operating Conditions*</b>	
Detector Ambient:	0 °C to 40 °C (32 °F to 104 °F)
Sampled Air:	0 °C to 40 °C (32 °F to 104 °F)
Humidity:	5% to 95% (non-condensing)
<b>Sampling Network</b>	
Maximum pipe lengths:	1 x 50 m (150 ft) (Max. 24 holes) 2 x 30 m (90 ft) per branch (Max. 12 holes per branch)
Sampling Hole Options:	Pre-Engineered Option or Maximum Pipe length in accordance with Pipe Modelling Design Tool (ASPIRE2™)

## Air Inlet Pipe

Accepts both metric and American standard pipe sizes.  
Metric: 25 mm American Pipe: IPS ¾ in.

## Area Coverage

Up to 500 m<sup>2</sup> (5000 sq. ft.) depending on local codes and standards

## Relay Outputs

3 changeover relays (Fire 1, Action, Fault), Contacts rated 2A @ 30 VDC (max).  
NO/NC Contacts

## Cable Access

3 x 25 mm (11/16 in.) cable entries (1 rear entry, 2 top entry)

## Cable Termination

Screw Terminals 0.2-2.5 mm<sup>2</sup> (30-12 AWG)

## Interfaces

Shown in Terminal Block Connections diagram, to right, plus an RS232 Programming Port.  
General Purpose Input (GPI) interface offers: Reset, Disable, Standby, Alarm set 1, Alarm set 2 and External Input functions.

## Alarm Threshold Setting Range

Alert, Action, 0.025 - 2.00% obs/m (0.008 - 0.625% obs/ft)

Fire 1, Fire 2 0.025 - 20.00% obs/m (0.008 - 6.25% obs/ft)

Individual Alarm Delays 0 – 60 seconds

Two Alarm Threshold Settings Either time or GPI based

## Display

• 4 Alarm State Indicators • Fault and Disabled Indicators

• Smoke Level Indicator • Instant Fault Finder

• Reset, Disable and Test Controls • Smoke and Flow AutoLearn Controls

## Event Log

Up to 18000 events, time and date stamped in separate, non-volatile, logs for:  
Smoke Level, Flow Level, Detector Status and Faults

## AutoLearn Smoke & Flow

• Automatically set acceptable alarm thresholds for both smoke and flow levels

• Minimum 15 minutes, maximum 15 days (default 14 days)

• During AutoLearn, thresholds are NOT changed from pre-set values

## Warranty Period

2 years

## Ordering Information:

VLF-500-00 Xtralis VESDA VLF. European language set. English display labels

VLF-500-01 Xtralis VESDA VLF. European language set. International display labels

VLF-500-02 Xtralis VESDA VLF. English + Asian language set. International display labels

VLF-500-04 Xtralis VESDA VLF. English + Russian language set. International display labels

VLF-500-05 Xtralis VESDA VLF. English + Eastern Euro language set. International display labels

VIC-010 VESDAnet Interface Card

VIC-020 Multifunction Control Card (MCC)





VIC-030 Multifunction Control Card (MCC) with Monitored Powered Output (MPO)

VSP-005 Filter Cartridge, VSP-715 Aspirator for VLF-500

# DISPLAY

The display provided to the user includes a Smoke Dial and alarm and status indicators.




When the field service access door is open, the user has access to the RESET , DISABLE , Fire Test , AutoLearn  and Instant Fault Finder functions. When the Instant Fault Finder function is activated, the Smoke Dial converts to a fault indicator, with the dial segment numbers corresponding to the faults listed below.

## LEGEND OF FAULT INDICATORS

1 Filter	6 External Device/PSU
2 Aspirator	7 Interface card
3 High flow	8 Field wiring
4 Low flow	9 AutoLearn Fail
5 n/a	10 Detector failure

## TERMINAL BLOCK CONNECTIONS



1 GPI	
2 GPI	
3 Display TX	
4 Display RX	
5 Display Common Ground	
6 Display Power -	
7 Display Power +	
8 Power Return 0 VDC	From power supply unit
9 Power In 24 VDC	
10 Power Return 0 VDC	To next detector (if more than 1 detector per Power Supply Unit)
11 Power Out 24 VDC	
12 NC	
13 Common	Fault relay
14 NO	
15 NC	
16 Common	Action relay
17 NO	
18 NC	
19 Common	Fire 1 relay
20 NO	

## APPROVALS COMPLIANCE

Please refer to the Product Guide for details regarding compliant design, installation and commissioning

